



## LED Floodlight

### Features:

Highly efficient replacement for conventional lightings.  
 Innovative design with a stylish contemporary look.  
 High-quality secondary optics with various beam angles  
 CCT available - 3500k / 4000k / 5000k / 6500k.  
 Extruded powder coated aluminum-alloy or pressure die-cast aluminium housing.  
 IP 65 enclosure; suitable for outdoor & indoor application.  
 Dimming : Optional.  
 Efficacy : 140 lm/W.  
 Suitable for various heights

**Application :** Open areas, industrial areas, sports complexes, high-masts

### Product specification:

Model No.	Unit	AG-LFL-150	AG-LFL-200	AG-LFL-250	AG-LFL-350	AG-LFL-400
Rated Power (Watts)	W	150	200	250	350	400
Total Lumens	lm	21000	28000	35000	49000	56000
Input Voltage	V <sub>ac</sub>	95-295	95-295	95-295	95-295	95-295
Frequency	HZ	50-60	50-60	50-60	50-60	50-60
THD	%	<10	<10	<10	<10	<10
PF		>0.95	>0.95	>0.95	>0.95	>0.95
CRI	R <sub>a</sub>	>75	>75	>75	>75	>75
IP Rating	IP	IP-65	IP-65	IP-65	IP-65	IP-65
Beam Angle	Degree	25/40/60/90	25/40/60/90	25/40/60/90	25/40/60/90	25/40/60/90