

Premium Version: 150L/W
Pre Version: 190-195L/W

**Plug & Play sensor :One step twist-on for smart dimming light
no worry about storage**

IP65
IP Rating

- ◆ Dimmable 0-10V / Microwave plug and play sensor module (Optional)
- ◆ Superior Heat Dissipation
- ◆ LED lifetime: L70 >60,000 hours @ 25°C fixture ambient
- ◆ Built-in 6kV surge protection
- ◆ IP65 waterproof with clear PC lens
- ◆ Application: Workshop, Warehouse | Parking Garage| Area Lighting

Patented Mold

LED Chips



High Efficacy SMD2835 LED

UL standard driver

High quality driver, integrated dimming function and built in 6KV surge protection with excellent performance and lifespan.






Excellent thermal management

system and heat radiation enable the LEDs consistently work cooler, providing significant boosts to lifetime and efficacy.



Beam Angle: 60°/90°/120°



Optional Accessories



Remote controller



Sensor module: Plug and play, twist on



Yoke Mount KITS



Pressure valve



85W/100W

Height 5-6m

100W

In-between distance 5-6m

125W/150W

Height 7-8m

150W

In-between distance 6-8m

200W

Height 9-10m

200W

In-between distance 8m

A. High Bay Lights



Twist-on sensor module tool free, plug and play. one model for sensor or no sensor.

B. High Bay with Microwave Sensors



Microwave Sensors :

Sensor direction: 180°




Sensor coverage: Φ 15M

Installation height: 6-12M




Product	AG- UHB- 85W	AG- UHB- 100W	AG- UHB- 125W	AG- UHB- 150W	AG- UHB- 200W	AG- UHB- 240W
Norminal Wattage	85W	100W	125W	150W	200W	240W
Size	ø270*115mm	ø270*115mm	ø270*115mm	ø305*115 mm	ø340*122 mm	ø340*122 mm
Input Voltage	200-240V AC 50/60Hz					
Features	Plug-play smart Sensors					
LED	SMD2835					
Driver	0-10V dimming, 10% minimum, SAA CE Listed					
Operating Temperature	-20 °C to +50 °C					
Power Factor(PF)	>0.9					
THD	<20%					
Lumen Output (+/- 5%)	16,575lm	19,500lm	24,375lm	28,500lm	38,000lm	45,600 lm
Luminaire efficacy (+/-5%)	150lm/w or 195lm/w (max)					
Ra	Ra70 or Ra80 is optional					
CCT	3000K/4000K /5000K/6000K					
SDCM	<6					
Beam Angle	60°/90°/120°					
Rating	IP65					
Material	Die-cast aluminum and PC					
Built in Surge protection	6KV					
Installation	Eye Bolt Mounting installation including 5' passed power cord					
Lumen Maintenance	> 60,000 hours-L ₇₀ at 25 °C					
Carton size	325*325*148mm	325*325*148mm	325*325*148mm	385*385*153mm	395*395*160mm	395*395*160mm
Packaging Type	1 unit /ctn					
Net weight	2.3kg	2.3kg	2.3kg	2.5kg	3.2kg	3.2kg
Gross weight	3.3kg	3.3kg	3.3kg	4.1kg	4.4kg	4.4kg

Installation Instruction:



Hanging ring installation



Hanging rod installation