



LED Floodlight

Features:

Highly efficient replacement for conventional lightings.
Innovative design with a stylish contemporary look.
High-quality secondary optics with various beam angles
CCT available - 3500k / 4000k / 5000k / 6500k.
Extruded powder coated aluminum-alloy or pressure die-cast aluminium housing.
IP 65 enclosure; suitable for outdoor & indoor application.
Dimming : Optional.
Efficacy : 140 lm/W.
Suitable for various heights

Application : Open areas, industrial areas, sports complexes, high-masts

Product specification:

Model No.	Unit	AG-FL-150	AG-FL-200	AG-FL-250	AG-FL-350	AG-FL-400
Rated Power (Watts)	W	150	200	250	350	400
Total Lumens	lm	21000	28000	35000	49000	56000
Input Voltage	V _{ac}	95-295	95-295	95-295	95-295	95-295
Frequency	HZ	50-60	50-60	50-60	50-60	50-60
THD	%	<10	<10	<10	<10	<10
PF		>0.95	>0.95	>0.95	>0.95	>0.95
CRI	R _a	>75	>75	>75	>75	>75
IP Rating	IP	IP-65	IP-65	IP-65	IP-65	IP-65
Beam Angle	Degree	25/40/60/90	25/40/60/90	25/40/60/90	25/40/60/90	25/40/60/90